

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number  
**WO 01/00092 A1**

- (51) International Patent Classification<sup>7</sup>: A61B 6/00 (74) Agent: E. BLUM & CO.; Vorderberg 11, CH-8044 Zürich (CH).
- (21) International Application Number: PCT/IB00/00725
- (22) International Filing Date: 29 May 2000 (29.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
99112248.2 25 June 1999 (25.06.1999) EP
- (71) Applicant (for all designated States except US): DDI DIRECT DIGITAL IMAGING GMBH [CH/CH]; Seidenhofstrasse 14, CH-6003 Luzern (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TRETIAKOV, Vjatcheslav [RU/RU]; Ivanova Street 30 A, Apt. 122, Novosibirsk, 630117 (RU). SKOK, Andrei [RU/RU]; Sirenevaja Street 23, Apt. 32, Novosibirsk, 630058 (RU). PORTMANN, Markus [CH/CH]; Mattmannhof, CH-6034 Inwil (CH). GEISSER, Albert [CH/CH]; Nasmannsbach 8, CH-6373 Ennetbürgen (CH).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DIGITAL X-RAY SCANNING APPARATUS



(57) Abstract: In order to improve an improved X-ray imaging quality an X-ray detector (14) is equipped with means (13, 15) for orienting it towards an X-ray source (2) during a scan (8a, 8b, 27). Means (9, 10, z) for reorienting a housing (10) comprising the X-ray detector (14) and a conventional cassette holder (4) and detector positioning means (9-12) cooperate to receive an X-ray beam (26a) with improved collimation quality. Thus the detection efficiency is increased, the image resolution is enhanced, and the beam exposure of patients (5) can be minimized. Embodiments relate to a linear X-ray detector (14) designed for serial readout of image pixels, a collimator (3, 3a, 3b) for both scanning and wide-aperture X-ray imaging, and a supporting arm (9) carrying the X-ray source (2), collimator (3) and detector arrangement (17).